No-Tox® Food Grade Air Line Lubricant

PRODUCT DESCRIPTION

Bel-Ray® No-Tox® Food Grade Air Line Lubricant is a versatile lubricant for air lines and pneumatic tools found in the "clean" industries such as food, beverage, pharmaceutical and personal care product manufacturing. It is designed to maximize air tool life and optimize pneumatic system performance by reducing wear, corrosion and deposits. No-Tox Food Grade Air Line Lubricant contains an emulsifier to remove water from the air distribution system and to optimize tool performance.

No-Tox Food Grade Air Line Lubricant is formulated with the highest quality USP white mineral oils and food grade additives that meet NSF H1 and FDA requirements for materials that may have incidental contact with food as defined under Title 21 CFR, 178.3570. It is Kosher and Pareve approved, as well as Halal certified. ISO 21469 certified food grade lubricant.

Nonfood Compounds
H1 Registered,
ISO 21469 Certified

PRODUCT FEATURES and BENEFITS

- NSF H1 registered for use where incidental food contact may occur.
- ISO 21469 certified
- Kosher and Pareve approved.
- Halal certified
- Bacteriological protection effectively inhibits the growth of certain bacteria, yeast, and mold in the lubricant.
- Excellent metal wetting capabilities created by the lubricant's strong film
- Enhanced anti-wear performance reduces friction and wear, maximizing tool life
- Superior rust protection and oxidation stability

APPLICATIONS

Bel-Ray No-Tox Food Grade Air Line Lubricant is recommended for pneumatic tools, air cylinders, air lubricators, and lightly loaded bearings.

DISTRIBUTED BY:
Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

4/30/2026

TECHNICAL DATA SHEET

PRODUCT DATA

Typical Properties		
Property	**Test Method**	**22**
ISO Viscosity Grade		22
Density @ 15°C (g/mL)	ASTM D4052	7.18
Viscosity @ 40°C (cSt)	ASTM D445	22.1
Viscosity @ 100°C (cSt)	ASTM D445	4.2
Viscosity Index	ASTM D2270	90
Flash Point, °C (°F)	ASTM D92	210 (410)
Pour Point, °C (°F)	ASTM D97	-18 (0)
Falex Pin & Vee Block Test Method B, non seizure load (lbf)	ASTM D3233	1750
Rust Preventation	ASTM D665A	Pass
Appearance		Clear
Color		Water-white to pale yellow

HEALTH and SAFETY

Health and safety recommendations for products can be found on the Safety Data Sheet (SDS) at www.belray.com

DISTRIBUTED BY:
Calumet Branded Products, LLC
1060 N Capitol Ave
Suite 6-401
Indianapolis, IN 46204
Technical Services: 317-328-5660
www.belray.com

To the best of our knowledge, the information contained herein is accurate, but is given without warranty or guarantee. We assume no liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of the suitability of any information or material for the use contemplated, the name in use and whether there is any infringement of patents is the sole responsibility of the user.

All trademarks are owned by one or more affiliates within the Calumet, Inc. organization, unless otherwise specified.

© 2026 Calumet, Inc.

4/30/2026