Accu-Lube® Synthetic
General Purpose MQL

FEATURES

- Replacement for straight oil
- Multi-purpose
- Water-based, synthetic lubricant
- Cools like flood coolant, lubricates like straight oil
- Rapid heat dissipation
- Clean before heat treating with rinse water

APPLICATIONS

- General machining, sawing and cutting
- For ferrous metals

DIRECTIONS

Fill Accu-Lube applicator reservoir above the low-level line. Refer to the Accu-Lube applicator manual for operating instructions.

HANDLING

Do not get in eyes. Wear eye protection/ face protection

STORAGE

Keep containers tightly closed in a dry, cool and well-ventilated place.

DISPOSAL

Dispose of in accordance with local regulations.



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid.
Odor	Mild.
Color	Blue.
pH Value	8.6
Flash Point	>212.0°F (>100.0°C)
Water Solubility	Soluble.
Specific Gravity	1.04
VOC Content	0% per US State and Federal Consumer Product Regulations
Pour Point	30°F (-1°C)
Viscosity	8 cSt @ 40°C

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
LBSYNT01	1 gal	bottle	4	36 lbs
LBSYNT55	55 gal	drum	1	499 lbs

CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!
800.241.8334 | www.itwprobrands.com
LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved