Hi-Spot Blue

HANDLING

- Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid prolonged exposure. Should be handled in closed systems, if possible. Provide adequate ventilation. Wear appropriate personal protection.

STORAGE

- Store locked up. Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

DISPOSAL

- Dispose of contents/container in accordance with local/regional/national/international regulations.

FEATURES

- Detects high spots on bearings, gears and other close fits
- Blue, soft, uniform paste spreads easily and evenly
- Never dries out
- Film remains pliable and transferable for months
- Saves time and money in surface scraping work



PHYSICAL PROPERTIES

Appearance / Physical State	Liquid.
Odor	Slight petroleum odor.
Flash Point	> 200.0 °F (> 93.3 °C)
VOC Content	0
Evaporation Rate	< 1 (BuAc = 1)
Vapor Density	> 1 (air = 1)
Prop 65 Warning	YES

AVAILABLE IN

Net Contents	Cnt. Type	Color	Units/ Case	Approx. Case Wt.	Part #
0.55 oz	tube	blue	36	2 lbs	83307

CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!
800.241.8334 | www.itwprobrands.com
LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved