Electro 140°
Contact Cleaner



FEATURES

- Non-flammable and non-conductive
- Safe on plastics
- Ideal for electrical/electronic fine parts
- Removes light greases, oils, dirt, and organic soils
- Fast Evaporating, no residue
- Quick Penetrating
- Conforms to VOC regulations in US and Canada
- Contoured can for improved hand grip

APPLICATIONS

- Calculators
- Communication Equipment
- Computers
- Digital Equipment
- Electrical Contacts
- Electrical Equipment
- Electronic Ignitions
- HVAC Systems
- Navigation Equipment
- Printed Circuit Boards
- Servers
- Switches & Relays
- Radars & Radios
- Robotic Equipment

SPECIFICATIONS AND APPROVALS

- Ford Motor Co.

PROPERTIES

Appearance / Physical State	Gas
Color	Clear, colorless.
Odor	Characteristic.
Melting / Freezing Point	N/A
Boiling Point / Range	383°F (195°C)
Flash Point	158°F (70°C) Tag Closed Cup
Evaporation Rate	< 0.1 BuAc
Flammability	Lower: 0.6%, Upper: 20.4% (estimated)
Vapor Pressure	<0.1 mm Hg @ 20°C
Vapor Density	6.1 (air = 1)
Water Solubility	Not soluble in water.
Partition Coefficient	>1
Auto-Ignition Temperature	>381.2°F (>194°C)
Viscosity	< 3 mm2/s
Heat of Combustion	> 30 kJ/g
Specific Gravity	0.84 - 0.86 @ 20°C (water=1)
VOC Content	0% per U.S. State and Federal Consumer Product Regulations
Propellant	Carbon Dioxide

DIRECTIONS

Hold can 6-8 inches (15-20 cm) away from electronic components and spray directly on surface to clean. May attack certain plastics.

HANDLING

Pressurized container: do not pierce or burn, even after use. Wash thoroughly after handling. Wear eye protection/face protection.

STORAGE

Protect from sunlight. Store in a well-ventilated place. Do not expose to temperatures exceeding 50oC/122oF. Keep away from heat, hot surface sparks, open flames, and other ignition sources.

DISPOSAL

Dispose of waste and residues in accordance with local authority requirements.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
00916	11 wt oz / 312 g / 389 mL	aerosol	12	12 lbs

CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!
800.241.8334 | www.itwprobrands.com
LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved