LPS® MAX CFC Free Contact Cleaner



FEATURES

- Plastic safe
- Fast evaporating, no residue
- Locking flip straw actuator
- Does not contain HCFCs
- Fast acting and fast penetrating
- Low odor
- Nozzle provides targeted or broad stroke application
- Embossed can for improved hand grip

APPLICATIONS

- Cables
- Circuit Breakers
- Electronic Motors
- Electronic Connectors
- Molds
- Nuts and Bolts
- Locks
- Power Tools
- Hinges
- Ignition Systems
- Relays

SPECIFICATIONS AND APPROVALS

- ASTM F-519, Type 1C
- Boeing D6-17487, Revision T
- Ford Motor Co.
- General Motors Co.
- NSF International,K2 (Aerosol)

PROPERTIES

Appearance / Physical State	Gas
Color	Clear water-white
Odor	Solvent
Boiling Point / Range	140.9 °F (60.5 °C) dispensed liquid
Flash Point	< 1.4°F (< -17.0°C) dispensed liquid
Evaporation Rate	< 1 (Ethyl Ether = 1)
Vapor Pressure	352.53 mm Hg @ 38°C
Vapor Density	~3 (air = 1)
Water Solubility	< 10% w/w
Partition Coefficient	>1
Auto-Ignition Temperature	582.8°F (306°C)
Viscosity	< 3 cSt @ 25°C
Heat of Combustion	> 30 kJ/g
Percent Volatile	100%
Specific Gravity	0.64 - 0.67 @ 20°C
VOC Content	96.2% per US State and Federal Consumer Product Regulations; 669 g/L per SCAQMD Rule 102
Prop 65 Warning	Yes

DIRECTIONS

Hold can 6-8 inches (15-20 cm) away and spray directly on surface to clean it. DO NOT USE ON ENERGIZED ELECTRICAL EQUIPMENT IN OPERATION AND ALLOW SURFACE TO DRY BEFORE RESTART.

HANDLING

Should be handled in closed systems, if possible. Vapors may form explosive mixtures with air. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Minimize fire risks from flammable and combustible materials (including combustible dust and static accumulating liquids) or dangerous reactions with incompatible materials. Use non-sparking tools and explosion-proof equipment.
Avoid contact during pregnancy/while nursing. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure.
Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains.

STORAGE

Store locked up. Keep away from heat, sparks and open flame. Eliminate sources of ignition.

Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Keep in an area equipped with sprinklers.

DISPOSAL

Dispose of contents/container in accordance with local/regional/national/international regulations.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
93116	11 wt oz / 312 g / 465 mL	aerosol	12	11 lbs

CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!
800.241.8334 | www.itwprobrands.com
LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved