LPS® MAX KB 88
Maximum Penetrant



FEATURES

- Heavy duty formulation bites through corrosion to free frozen parts quickly
- Displaces moisture
- Kb solvency value of 151
- Advanced penetration formula frees frozen parts faster
- VOC compliant in all 50 states
- Locking flip straw actuator
- Nozzle provides targeted or broad stroke application
- Embossed can for improved hand grip

APPLICATIONS

- Frozen nuts & bolts
- Chains
- Corroded fasteners
- Equipment disassembly
- Hinges
- Plumbing Fixtures
- Shafts
- Conveyors
- Frozen gears & cogs
- Bearings
- Screws
- Pulleys
- Engines & electric motors
- Relays

SPECIFICATIONS AND APPROVALS

- A-A-50493D, Class B, Type II
- NSF International, H2

PROPERTIES

Appearance / Physical State	Compressed Gas
Color	Red
Water Solubility	immiscible
Density	0.85-0.90
VOC Content	24% per US State and Federal Consumer Product Regulations
Prop 65 Warning	Yes

HANDLING

Avoid all personal contact, including inhalation.
Wear protective clothing when risk of exposure occurs.
Use in a well-ventilated area.
Prevent concentration in hollows and sumps.
DO NOT enter confined spaces until atmosphere has been checked.
Avoid smoking, naked lights or ignition sources.
Avoid contact with incompatible materials.
When handling, DO NOT eat, drink or smoke.
DO NOT incinerate or puncture aerosol cans.
DO NOT spray directly on humans, exposed food or food utensils.
Avoid physical damage to containers.
Always wash hands with soap and water after handling.
Work clothes should be laundered separately.
Use good occupational work practice.
Observe manufacturer's storage and handling recommendations.
Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.

STORAGE

Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can
Store in original containers in approved flammable liquid storage area.
DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
No smoking, naked lights, heat or ignition sources.
Keep containers securely sealed. Contents under pressure.
Store away from incompatible materials.
Store in a cool, dry, well ventilated area.
Avoid storage at temperatures higher than 40°C.
Store in an upright position.
Protect containers against physical damage.
Check regularly for spills and leaks.
Observe manufacturer's storage and handling recommendations.
NFPA 30B Storage Level: 3

DISPOSAL

Consult State Land Waste Management Authority for disposal.
Discharge contents of damaged aerosol cans at an approved site.
Allow small quantities to evaporate.
DO NOT incinerate or puncture aerosol cans.
Bury residues and emptied aerosol cans at an approved site.

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Case Weight
92316	13 wt oz / 369 g / 417 mL	aerosol	12	12 lbs

CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!
800.241.8334 | www.itwprobrands.com
LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved