Magnum

Premium Lubricant with PTFE



FEATURES

- High performance, long lasting lubricant with PTFE additives
- Penetrates and protects metal against rust and corrosion up to 1 year indoors
- Extends equipment life
- Performs in extreme conditions
- Safe to use on most surfaces
- Does not contain silicone
- Contoured can for improved hand grip

APPLICATIONS

- Bearings & Valves
- Cables & Linkages
- Dies, Bits & Fasteners
- Engines & Electric Motors
- Hoists, Lifts & Draglines
- Metal Parts & Hand Tools
- Parts in Storage
- Production & Transportation Equipment
- Pulleys and rollers
- Slides and tracks

SPECIFICATIONS AND APPROVALS

- NSF International, H2 (Aerosol)
- NSF International, H2 (Bulk)

PROPERTIES

Appearance / Physical State	Aerosol: Gas, Bulk: Liquid
Color	Brown
Odor	Mild. Sweet.
Boiling Point / Range	383°F (195°C)
Flash Point	174.2°F (79.0°C) Tag Closed Cup - dispensed liquid
Evaporation Rate	< 0.1 BuAc
Flammability	Flammability limit: Lower = 0.6%, Upper = 7%
Vapor Pressure	< 0.05 mm Hg @ 20ºC
Vapor density	4.7 (air = 1)
Water Solubility	<4%
Partition Coefficient	< 1
Auto-Ignition Temperature	> 442.4°F (> 228°C)
Viscosity	< 7 cSt @ 25ºC
Specific Gravity	0.85 - 0.87 @ 20ºC
VOC Content	Aerosol: 2.9%; Bulk: 3.0%
Propellant	Carbon Dioxide
Temperature Range	-60°F – 300°F (-51°C – 149°C)

DIRECTIONS

Shake well before using. Apply on clean surface when possible. Spray in even coats and reapply as needed.

HANDLING

DO NOT spray into or around ignition sources. DO NOT allow material to come in contact with eyes or skin. Wear appropriate protective equipment during handling. Keep container closed. Avoid breathing vapors or mists. Use only with adequate ventilation. Wash thoroughly after handling.

STORAGE

Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store between 40°F and 120°F (4.4°C and 49°C). Protect from freezing. Store aerosols as Level 3 Aerosol (NFPA 30B). Store all materials in a dry, well-ventilated area. Avoid breathing vapors.

DISPOSAL

Waste must be disposed of in accordance with any and all applicable environmental control rules and/or regulations

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
00616	11 wt oz / 312 g / 358 mL	aerosol	12	12 lbs
00605	5 gal / 18.93 L	pail	1	41 lbs

CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved