Red & Redi

Multi-Purpose Red Grease



FEATURES

- Reduces friction and vibration at extreme pressures and temperatures
- Red color is highly visible during and after lubrication
- Prevents rust, corrosion, and oxidation
- Water resistant formula prevents water washout
- Resists shock
- Non-melting
- NLGI Grade 2

APPLICATIONS

- Automotive
- Aviation
- Cables
- Cams and Pistons
- Chains
- Guide Rails
- Latches
- Marine
- Open Gears
- Overhead Door Tracks
- Packaging
- Slide Conveyors

PROPERTIES

Appearance / Physical State	Gas/Aerosol
Color	Red
Propellant	Liquefied Petroleum Gas (LPG)
VOC Content	9.7%
Base Oil Type	Semi-synthetic
NLGI Grade	2
Thickener Type	Fumed silica
Dropping Point	None
Temperature Range	10 to 525°F (-12 to 274°C)
4-Ball Weld Load	>205 kg

DIRECTIONS

Shake well before using to insure proper mixing. Spray a thin film on the surface to be lubricated or protected. To apply to hard to reach areas, insert the extension tube provided into valve cap. A thicken grease will form within seconds after application.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. (See Section 7 of the SDS)

STORAGE

Level 3 Aerosol. Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C/122°F. (See Section 7 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance with local/regional/national/international regulations. (See Section 13 of the SDS)

AVAILABLE PRODUCTS

Part No.			Net Contents	Container Type	Units/Case	Approximate Case Weight
US	Canada	Europe				
05816	C05816	M05816	11 wt oz / 312 g / 451 mL	aerosol	12	12 lbs

CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved