Rustlick™ B
Rust Preventative

DESCRIPTION

Rustlick™ B Rust Preventative is a non-flammable water-soluble corrosion inhibitor designed to prevent in-process rusting of ferrous metals. It leaves a non-oily, dry, microscopic protective film and can be used for hydrostatic testing and vibratory finishing. Biodegradable, transparent, and non-irritating, **Rustlick B** is not subject to bacterial decomposition or rancidity and does not require removal prior to painting, plating, or assembly.



FEATURES

- Use for short-term indoor storage ; prevents flash rusting
- No cleaning required before painting or plating
- Can be used for sand blasting or vibratory finishing

APPLICATIONS

- For short-term corrosion prevention

HANDLING

Ensure adequate ventilation. Do not get in eyes, on skin, or on clothing. Do not breathe vapors or spray mist. Wear personal protective equipment. Wash thoroughly after handling.

STORAGE

Keep container tightly closed. Store in original container. Keep locked-up.

DISPOSAL

This material, as supplied, is not a hazardous waste according to Federal regulations (40CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

PROPERTIES

Appearance / Physical State	Liquid.
Color	Green.
Odor	Amine-like.
pH Value	9.1 @ 10%
Boiling Point / Range	212°F (100°C)
Flash Point	>199.4°F (>93.0°C) Pensky-Martens Closed Cup
Evaporation Rate	<1
Vapor density	>1
Density	9.1 lb/gal (1089 kg/m^3)
Water Solubility	Soluble.
Specific Gravity	1.05
Dilution Ratio	Hydrostatic and immersion testing, rinsing, washing, tumbling: 10:1-30:1
Refractometer Readings	10:1 (10%) = 4.0 20:1 (5%) = 2.0 30:1 (3%) = 1.3

SHELF LIFE INFORMATION

1 year

AVAILABLE PRODUCTS

Part No.	Net Contents	Container Type	Units/Case	Approximate Case Weight
73011	1 gal	container	4	40 lbs
73051	5 gal	pail	1	48 lbs
73551	55 gal	drum	1	522 lbs

CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!
800.241.8334 | www.itwprobrands.com
LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved